



Optional 3-Unit Rack Mount

The DS3/E3 Passive Network Tap provides a “coding-scheme independent” solution to access your DS3 or E3 WAN network for analysis without interruption. The totally passive and fault tolerant design ensures network uptime and will not impact network performance.

The DS3/E3 Passive Network Taps the perfect companion for the Datacom Systems DS3 Switch. The tap also works seamlessly with portable analyzers - just walk up and plug in.

- Suitable for DS3/E3/T3 networks
- Eliminates the need to disconnect and reconnect your tools each time a network segment needs to be analyzed
- View ALL seven layers of network traffic
- View ALL traffic on both sides of links
- Rack-mount up to 3 units (at 1U) and up to 14 units (at 4U).
- Passive non-powered design
- Easily deploy with many WAN topologies, including ATM, ClearChannel, and Frame Relay

TECHNICAL SPECIFICATIONS

Ports

- One (1) DS3 or E3 BNC Network Connection
- One (1) DS3 or E3 BNC Tap/Monitoring Connection

Physical Dimensions (H x W x D)

- 1.07 x 5 x 5 in.
- 2.7 x 12.7 x 12.7 cm.

Weight

- 15 oz.
- .43 Kgs.

Environmental

- Operating Temperature: 0° to 40° C
- Storage Temperature: 30° to 65° C
- Humidity: Less than 95° C non-condensing

Warranty

- 2-year limited warranty

Ordering Information

Product	Description
DS3/E3-PT	DS3/E3 Passive Tap
RMC-3	3-Unit Rack Mount
RMC-14	14-Unit Rack Mount