



Optional 2-Unit (19 Inch) Rack Mount

The F50/50/50-4LCM-10G Quad Fiber 10Gigabit passive TAP provides permanent access into four multi-mode fiber links. This network TAP is ideal for security applications, network monitoring and anywhere you need to see all the data that only an In-Line solution can provide. Invisible to the network and non-powered, fiber TAPs will not affect network performance or integrity.

- Passive, non-powered design
- Four TAPs allow you to connect to one tool per link; tools require a dual NIC card to receive both sides of the conversation
- Supports multiple topologies, including Gigabit Ethernet, ATM, OC3-OC192 and SONET
- View layer 1 and 2 errors not seen when performing network monitoring using SPAN ports
- Available with custom split ratios upon request
- Space saving design allows you to TAP up to eight links in 1U

TECHNICAL SPECIFICATIONS

TAP Connections	
Four Links Tapped Dual LC	
Monitor Ports	
Four Tools Dual LC	
Split Ratio	
50/50	
Additional Split Ratios Available	
Insertion Loss	
4.0 dB Insertion Loss Max.	
Physical Dimensions (HxWxD)	
1.13 x 8.75 x 7.75 in (2.86 x 22.22 x 19.69 cm)	
Weight	
1.10 lbs (0.49 kgs)	
Environmental	
Operating Temperature: 32° to 104°F (0° to 40°C)	
Storage Temperature: -22° to 149°F (-30° to 65°C)	
Humidity: 5 to 90% non-condensing	
Warranty	
Two (2) Year Limited Warranty	
Order Information	
Product	Description
F50/50/50-4LCM-10G	Quad Fiber 10Gigabit Passive TAP (50 micron) 50/50 split ratio
RMC-2	2 Tap 1U Rack Mount Chassis

ACCESS YOUR NETWORK™