



Optional 2-Unit (19 Inch) Rack Mount

The F50/50/62-4LCM-10G Quad Fiber 10Gigabit passive TAP provides permanent access into four multi-mode fiber links. This network TAP is ideal for security applications, network monitoring and anywhere you need to see all the data that only an In-Line solution can provide. Invisible to the network and non-powered, fiber TAPs will not affect network performance or integrity.

- Passive, non-powered design
- Four TAPs allow you to connect to one tool per link; tools require a dual NIC card to receive both sides of the conversation
- Supports multiple topologies, including Gigabit Ethernet, ATM, OC3-OC192 and SONET
- View layer 1 and 2 errors not seen when performing network monitoring using SPAN ports
- Available with custom split ratios upon request
- Space saving design allows you to TAP up to eight links in 1U

## TECHNICAL SPECIFICATIONS

### TAP Connections

Four Links Tapped Dual LC

### Monitor Ports

Four Tools Dual LC

### Split Ratio

50/50

Additional Split Ratios Available

### Insertion Loss

4.0 dB Insertion Loss Max.

### Physical Dimensions (HxWxD)

1.13 x 8.75 x 7.75 in (2.86 x 22.22 x 19.69 cm)

### Weight

1.1 lbs (0.49 kgs)

### Environmental

Operating Temperature: 32° to 104°F (0° to 40°C)

Storage Temperature: -22° to 149°F (-30° to 65°C )

Humidity: 5 to 90% non-condensing

### Warranty

Two (2) Year Limited Warranty

### Order Information

Product	Description
F50/50/62-4LCM	Quad Fiber 10Gigabit Passive TAP (62.5 micron) 50/50 split ratio
RMC-2	2 Tap 1U Rack Mount Chassis

## ACCESS YOUR NETWORK™