



Optional 3-Unit Rack Mount

The T1/E1 Passive Network Tap is a single port device that provides easy, 24 x 7 access to a T1/E1 segment. The T1/E1 Passive Tap's design is non-powered, so it will ensure that network performance and integrity will not be affected by power loss. Use with portable or distributed T1 analyzers, intrusion detection devices, probes, and monitoring devices.

- Permanent tapped access eliminates the need for network connectors to be disconnected and connected each time a network segment needs to be monitored
- Non-powered passive tap design for total fault tolerance - network will never be interrupted due to power loss or network tap failure
- T1/E1 network taps provide In-Line access to critical T1/E1 links for monitoring of WAN traffic
- T1/E1 taps are Ideal for Security and Monitoring applications
- View ALL seven layers of network traffic
- Improve the ROI of your Network Tools
- Comes with convenient built-in rack-mount or use an optional rack mount package to mount 3 units (at 1U) and up to 14 units (at 4U).

TECHNICAL SPECIFICATIONS

Ports

- One (1) T1 or E1 Tap (RJ48C) Network Connections
- One (1) T1 or E1 Tap (RJ48C) Tap/Monitoring Connection

Insertion Loss

-3.5 dB

Physical Dimensions (H x W x D)

1.07 x 5 x 5 in.
2.7 x 12.7 x 12.7 cm.

Weight

12 oz.
.34 Kgs.

Environmental

Operating Temperature: 0° to 40° C
Storage Temperature: 30° to 65° C
Humidity: Less than 95° C non-condensing

Warranty

2-year limited warranty

Ordering Information

Product	Description
T1/E1-PT	T1/E1 Passive Tap
RMC-3	3-Unit Rack Mount
RMC-14	14-Unit Rack Mount